



SIDE-O-MATIC™ 93 and 110 Series Telescoping Trolley Booms

USTC's SIDE-O-MATIC™ three-section telescoping trolley booms are ideal for unloading with hook travel to within 14 inches of the pedestal without elevation. Long telescoping reach enables exact placement of the load. Auto Level Lift assures the load distance automatically remains constant in relationship to the trolley when telescoping in or out. Lift and trolley cylinders are located on top and inside the boom for protection against job-site elements. Super smooth



MODEL 110-26 E

MODEL 93-26 C



telescope action achieved through proven double and triple roller design, with no wear pads to replace. Dual remote control systems assure optimum "up-time" and provides operator protection against electrical hazards. Rugged Eagle pedestal for truck mounting protects hydraulic and electrical components and makes them easily accessible for maintenance. The Classic pedestal, designed for trailer installation, requires no cutting or fitting and quickly bolts to the trailer frame. An 18 horsepower auxiliary gas engine is an option to PTO operation. All USTC products are backed by USTC's unparalleled full one year warranty and sold and serviced by our world-wide factory-trained Distributor network.

- Twin elevate cylinders reduce boom twist and side loading effects.
- Proven pistol grip radio remote and patented SHOCK GUARD® pneumatic system provide dual control.
- Boom constructed of high alloy steel for increased strength to weight ratio.
- Continuous boom rotation with high torque 30:1 reduction gear box and ball bearing ring gear.
- Low pressure, open-center hydraulic valves provides longer component wear and reduced hydraulic maintenance.
- Flow divider allows the SIDE-O-MATIC™ to perform several functions simultaneously and efficiently.
- Pilot operated load holding valves on lift and elevate cylinders prevent accidental load fall should a hydraulic line burst.
- Optional hydraulic outriggers for increased stability.
- Designed for truck or trailer installation.
- Wide variety of forks and lifting devices available.
- Optional bearing risers provide increased load clearance under boom.
- Local factory-trained and authorized distribution, installation and service.
- Full twelve (12) month warranty.
- American Made.

THE OPERATOR'S CHOICE